

VPFC Calcium Fluoride Crystal Infrared Windows

Versatile Port for Ultrasound and IR Inspection

Calcium Fluoride (CaF₂) has long been used in research applications. It is a cost-effective solution and performs well in controlled environments where humidity, chemical exposure, vibration and high frequency noise are minimized or eliminated.

The transmission rate characteristics of CaF₂ are ideal for higher temperature applications, short and medium wave thermography and for the visual spectrum. Medium wave transmission rates (7-14 micron) are typically between 50% and 65%, based on the infrared camera detector sensitivities at different wavelengths.

IRISS VPFC infrared windows are specially coated to reduce the transmission drift due to moisture/humidity. However, industrial users are strongly encouraged to investigate the IRISS VPFR series of Industrial-Grade Infrared Windows which are specifically designed for stability in harsh industrial environments.



Specifications

Materials	
Window housing and cover	UL 94 5VA Nylon ("switchgear-grade plastic"); -40°C (-40°F) to 273°C (523°F)
Optic	Calcium Fluoride Crystal (other crystal options also available) -100°C (-148°F) to 1400°C (2555°F)
Gaskets	UL 94 5VA TPE; -40°C (-40°F) to 273°C (523°F)
Hardware	316 stainless steel
Other	
Useful temperature rating	-40°C (-40°F) to 200°C (392°F)
Water and dust ingress	IP65 / NEMA 4: closed and when in use

Dimensions

Model	Body diameter	Viewing area diameter	Assembly thickness
VPFC-50	9.1 cm (3.6 in)	5.1 cm (2 in)	2.6 cm (1.0 in)
VPFC-75	12.1 cm (4.8 in)	7.6 cm (3 in)	2.6 cm (1.0 in)
VPFC-100	15.1 cm (5.95 in)	10.2 cm (4 in)	2.6 cm (1.0 in)

Ordering information


Order #	Description	Price
VPFC-50	Industrial-grade infrared window: 9.1cm (2.0 in) diameter viewing area	POA
VPFC-75	Industrial-grade infrared window: 7.6 cm (3 in) diameter viewing area	POA
VPFC-100	Industrial-grade infrared window: 10.2 cm (4 in) diameter viewing area	POA

VPFC Features

- Transparent crystal allows for visual inspection (however does not meet impact requirements of IEEE for medium and high voltage switchgear).
- Compatible with all models of infrared cameras.
- Ultraviolet transmission compatible with all models of corona cameras.
- Housing made of "switchgear-grade" plastics: insulated to 30kV/mm, non-conductive, and UL94 compliant.

Certifications

- UL 50V
- UL 508A; ANSI UL 508A
- IP65 / NEMA 4
- Lloyds of London Type Approval



For more information visit www.iriss.com or contact your local agent

IRISS
See What You've Been Missing!

www.iriss.com
E-mail: info@iriss.com
US Toll Free (877) 70 IRISS
International +1 (941) 907 9128

©2011 IRISS, Inc. All rights reserved. Prices and specifications subject to change without notice. Printed in U.S.A.